



### SPRAY FOAM INSULATION REQUEST

### SPRAY-APPLIED RIGID POLYURETHANE FOAM INSULATION

Address/Land Location: _____		BP Number (office use only)
Municipality: _____		
Product	CCMC Listing or Report #: _____ Manufacturer: _____ Colour: _____	
	CCMC approved for use as: <input type="checkbox"/> Insulation <input type="checkbox"/> Vapour Barrier <input type="checkbox"/> Air Barrier <input type="checkbox"/> Low Density (open cell) <input type="checkbox"/> Medium Density (closed cell) <input type="checkbox"/> Type 1 <input type="checkbox"/> Type 2	
RSI/mm (or R/in): _____		
Thermal Barrier	Foamed plastics must be protected with a thermal barrier such as: drywall; an interior finish listed in subsections 9.29.4 to 9.29.9; or a material that meets the requirements of classification B when tested in conformance with CAN/ULC-S124 ( <b>See Spray Thermal Barrier Request Form</b> ). Product used for thermal barrier: _____ Thickness of thermal barrier: _____	
Vapour Permeance	Will the spray foam insulation form a vapour barrier? <input type="checkbox"/> Yes <input type="checkbox"/> No Minimum thickness to attain a water vapour permeance of 60 ng/Pa*s*m <sup>2</sup> : _____	
Application	Where will the spray foam be applied? _____ _____ _____	Thickness (mm) _____ _____ _____
Special Circumstances	Have the plans, details and specifications been reviewed and sealed by a design professional (Architect or Professional Engineer)? <input type="checkbox"/> Yes <input type="checkbox"/> No When spray foam insulation is applied to the underside of the roof sheathing in an attic, and in similar enclosed spaces, the area is required to be conditioned and vented. Indicate how this requirement will be met: _____	
Safety	Buildings cannot be occupied for 24 hours after the installation of spray-applied rigid polyurethane insulation. The general contractor is to ensure inspections are booked for at least 24 hours after spray foam insulation installation is finished.	
Site Requirements	It is the contractor's responsibility to ensure a label is placed on the job site as required by CAN/ULC- S705.2 including the above information and stating: "This certificate indicates that the installed spray-applied rigid polyurethane foam insulation meets the CAN/ULC-S705.1 – medium density – product standard. This product has been installed according to the CAN/ULC-S705.2 installation standard."	
Installer	Installing Company: _____	Date: _____
	Certified Installer: _____	ID #: _____
	Signed By (Print): _____	Signature: _____
	Email Address: _____	Phone Number: _____